

1 What is claimed is:

2
3 1. A wrapping material suitable for making a smoking article, the wrapping material
4 comprising:

5 a smoking article wrapping material substrate having a plurality of bands of coating
6 layers deposited in a pattern on the substrate, at least one of the coating layers applied by
7 spraying.

8
9 2. The wrapping material of claim 1, wherein the wrapping material is adapted to be useful
10 in manufacture of a reduced ignition propensity cigarette.

11
12 3. The wrapping material of claim 1, wherein the coating pattern comprises transverse
13 bands of coating layers, each band having a longitudinal width and spaced apart along a
14 longitudinal length of the wrapping material.

15
16 4. The wrapping material of claim 1, wherein the coating layers comprise coatings applied
17 in pre-determined amounts.

18
19 5. The wrapping material of claim 1, wherein the coating layers are applied to the substrate
20 online during the making of the smoking article.

21
22 6. A wrapping material suitable for making a smoking article, the wrapping material
23 comprising:

24 a smoking article wrapping material substrate having a plurality of bands of coating
25 layers deposited in a pattern on the substrate, at least one of the coating layers applied by ink jet
26 coating.

27
28 7. The wrapping material of claim 6, wherein the wrapping material is adapted to be useful
29 in manufacture of a reduced ignition propensity cigarette.

1 8. The wrapping material of claim 6, wherein the coating pattern comprises transverse
2 bands of coating layers, each band having a longitudinal width and spaced apart along a
3 longitudinal length of the wrapping material.

4
5 9. The wrapping material of claim 6, wherein the coating layers comprise coatings applied
6 in pre-determined amounts.

7
8 10. The wrapping material of claim 6, wherein the coating layers are applied to the substrate
9 online during the making of the smoking article.

10
11 11. A smoking article having reduced ignition propensity, the smoking article comprising a
12 smokable material disposed in a wrapping material, the wrapping material comprising:

13 a smoking article wrapping material substrate having a plurality of bands of coating
14 layers deposited in a pattern on the substrate, at least one of the coating layers applied by
15 spraying,

16 wherein each of the plurality of bands comprises (a) a first coating layer effective in
17 reducing the inherent porosity of the substrate, and (b) a second coating layer overlying the first
18 coating layer.

19
20 12. A smoking article having reduced ignition propensity, the smoking article comprising a
21 smokable material disposed in a wrapping material, the wrapping material comprising:

22 a smoking article wrapping material substrate having a plurality of bands of coating
23 layers deposited in a pattern on the substrate, at least one of the coating layers applied by ink jet
24 coating,

25 wherein each of the plurality of bands comprises (a) a first coating layer effective in
26 reducing the inherent porosity of the substrate, and (b) a second coating layer overlying the first
27 coating layer.

28
29 13. A method of making a smoking article wrapping material, the method comprising:
30 providing a smoking article wrapping material substrate wound on a first roll;
31 unwinding the substrate from the first roll;

1 applying in a pattern on the substrate a plurality of bands of coating layers comprising (a)
2 a first coating layer effective in reducing the inherent porosity of the substrate, and (b) a second
3 coating layer overlying the first coating layer, at least one of the coating layers applied by
4 spraying.

5
6 14. The method of claim 13, wherein the bands of coating layers are applied to the substrate
7 online during making of a smoking article.

8
9 15. The method of claim 13, further comprising winding the wrapping material substrate onto
10 a second roll,

11 wherein the bands of coating layers are applied to the substrate offline prior to making of
12 a smoking article.

13
14 16. A method of making a smoking article wrapping material, the method comprising:
15 providing a smoking article wrapping material substrate wound on a first roll;
16 unwinding the substrate from the first roll;
17 applying in a pattern on the substrate a plurality of bands of coating layers comprising (a)
18 a first coating layer effective in reducing the inherent porosity of the substrate, and (b) a second
19 coating layer overlying the first coating layer, at least one of the coating layers applied by ink jet
20 coating.

21
22 17. The method of claim 16, wherein the bands of coating layers are applied to the substrate
23 online during making of a smoking article.

24
25 18. The method of claim 16, further comprising winding the wrapping material substrate onto
26 a second roll,

27 wherein the bands of coating layers are applied to the substrate offline prior to making of
28 a smoking article.